



Sinidex Stays by Abacus

The Sinidex stays offer improved security and weather sealing through the use of a Nylon reduced friction end cap. These stays have been designed to offer smooth closure and higher performance for window applications of all sizes.

- Available in 8, 10, 12", 16", 20" and 24" top hung and 12" and 16" for side hung applications.
- Manufactured using high-grade Austenitic and Ferretic stainless steel.
- The stays have been proven to a lifetime 30,000 cycle guarantee

RECOMMENDED MAXIMUM WINDOW WEIGHTS & SIZES

PRODUCT	SIZE INS	SIZE MM	APPLICATION	WINDOW SIZE APPROX WIDTH MM	WINDOW SIZE APPROX HEIGHT MM	WINDOW WEIGHT APPROX KG	STACK HEIGHT MM	OPENING ANGLE
HS 08/WS	8	210	TOP HUNG	1200	300	10	13/14 & 16/17	62
HS10/WS	10	260	TOP HUNG	1200	450	16	13/14 & 16/17	90
HS12/WS	12	311	TOP HUNG	1200	600	21	13/14 & 16/17	86
HS16/WS	16	406	TOP HUNG	1200	750	22	13/14 & 16/17	83
HS16/WS	16	406	SIDE HUNG	700	1300	26	13/14 & 16/17	83
HS20/WS	20	511	TOP HUNG	1200	900	24	13/14 & 16/17	42
HS24/WS	24	615	TOP HUNG	1200	1500	50	13/14 & 16/17	38
HSS12/WS	12	311	SIDE HUNG	650	1250	20	13/14 & 16/17	86
SP254/WS	10	254	EGRESS ONLY	500	1200	18	13/14 & 16/17	80
SP316/WS	16	406	EGRESS ONLY	600	1200	21	13/14 & 16/17	84

IT IS THE RESPONSIBILITY OF THE WINDOW MANUFACTURER TO ENSURE THAT THE FINISHED WINDOW MEET ANY REQUIRED SAFETY AND PERFORMANCE SPECIFICATIONS

Cotswold Architectural Products Ltd. Manor Park Industrial Estate, Manor Road, Cheltenham, Gloucestershire, GL51 9SQ.
Tel: (01242) 233993 Sales Tel: (01242) 246624 Sales Fax: (01242) 221146 www.cotswold-windows.co.uk 26.04.10